

## Q2PTD/CE

**Electronic Dual Pump control panel for operating and protecting two three phase submersible pumps.**

### FEATURES

- Display of all parameters
- Operation with pressure transducer, Tank emptying with transducer, Cavitation protection
- Dry run protection
- Adjustable pressure for the starting of second pump.
- Automatic duty standby change over.
- 400V/3ph 50HZ
- Power Isolator switch
- Auto / Off / Manual switch
- Motor overloads
- Current transformer
- Voltage transformer
- Remote operation contacts
- Phase failure
- Fault buzzer
- LCD display
- Fault and run lights
- Pump Stop/ Start buttons



### OPERATING CONDITIONS

- Degree of protection : IP55
- Field of operation : -5°C + 40°C
- Relative humidity : 50% with temperature of 40°C

Pressure Transducer: TP1 0-10 Bar & 0-20 Bar.

CODE	Control Panel Type	Max Power to 400 V Three Phase		Max Amps protection (adjustable)	Dimensions in mm			Weight Kg
		KW	HP		H	W	D	
700235	Q2PT/CE 50 400-	3	4	25A	330	225	145	3.6
700240	Q2PT/CE 550 750-	5.5	7.5	25A	330	225	145	3.61
700245	Q2PT/CE 1000-	7.5	10	25A	330	225	145	3.6