
LIQUID-SPECIFIC PRODUCT LINE SERIES: 34 CAST IRON CONSTRUCTION

FEATURES & BENEFITS

- Fully jacketed pump to rapidly deliver heat directly to the stuffing box, casing and head.
- Jacketing suitable for hot oil or steam for enhanced application flexibility
- Simple, economical design for transfer and delivery of asphalt and bitumen at low to moderate pressures














28 to 250,000 SSU (1 to 55,000 cSt)








PERFORMANCE

MODELS	SPECIFICATIONS							
Jacketed		Performance	Standard Ports					
Packing	Max Speed, RPM	GPM	m³/h	Size, Inches	Туре			
LQ34	420	90	20	2.5	Flange			
Q34	350	200	45	3	Flange			
M34	280	280	64	4	Flange			
N34	280	450	102	5	Flange			

CURVES



PORTING

Right Angle (90°)

Flanged

SEALING

Packing

MOUNTING

Foot Mount

OPTIONS

- Jacketed Internal Relief Valve
- Hardened Part Options
- Plain Head for Externally Lubricated Idler Pin

DRIVES



Purchased Gear Reducer Drive

V) V-Belt Drive

TYPICAL APPLICATIONS

- Asphalt
- Bitumen
- Tar

Pitch

- Bunker Oils
- Residual Oils

VIKING PUMP[®]

VIKING PUMP, INC. A Unit of IDEX Corporation 406 State Street Cedar Falls, Iowa 50613 U.S.A. vikingpump.com



0508 4 BBENG www.brownbros.co.nz

United States vikingpump.com	Canada vikingpumpcanada.com	Europe & Africa vikingpump.com	Asia-Pacific idexfmt-asia.com		Middle East vikingpump.com	Latin America vikingpump.com	Australia & New Zealand vikingpump.com
Cedar Falls, Iowa Phone: (319) 266-1741	Windsor, Ontario Phone: (519) 256-5438	Shannon, Ireland Phone: +353 (61) 471933	China - Shanghai Phone: +86-21-5241-5599	India - Mumbai Phone: +91-22-6643-5563	Dubai, UAE Phone: +971 4 2600300		
			Singapore				IREX