


UNIVERSAL PRODUCT LINE

SERIES: 224A, 4224A, 4224B, 324A, 4324A

CAST IRON CONSTRUCTION

FEATURES & BENEFITS

- Rugged and reliable, yet economical
- Widest range of sizes and options available to suit almost any non-corrosive application
- Integral jacket chambers in the bracket and head surround the seal and pump internals for rapid & efficient heating using steam or hot oil



Behind the Rotor Seal

Component Seal

Cartridge Seal

Seal chamber accepts packing and a variety of component and cartridge style mechanical and lip seals, in both single and double mechanical seal configurations; behind the rotor seal (4224B) option also available


Double row ball or tapered roller bearings for axial thrust control

Threaded one-piece bearing housing allows for easy end clearance adjustment

M4224A

Large diameter threaded bearing housing allows easy removal of cartridge seals (not 4224B)

Jacketing for steam, hot oil, or water circulation to maintain a constant temperature



Rotor

Idler

Multiple port sizes, types, and ratings are available including threaded and flanged (Class 125, Class 250)

One-piece cast bracket with seal between bearings provides rigid foundation to maximize seal and bearing life



CAPACITY

to 1,600 GPM
(363 m³/h)



PRESSURE

to 200 PSI
(14 BAR)



TEMPERATURE

-60°F to +450°F
(-50°C to +230°C)



VISCOSITY

28 to 2,000,000 SSU
(0.1 to 440,000 cSt)




VIKING PUMP®

PERFORMANCE

MODELS			SPECIFICATIONS					
Jacketed			Nominal Pump Rating (100 SSU & Below)			Standard Ports		
Packed Gland	Mechanical Seal	Behind the Rotor Seal	Max Speed, RPM	GPM	m ³ /h	Size, Inches	Type	
H224A	H4224A	H4224B	1750	15	3.5	1.5	NPT	
HL224A	HL4224A	HL4224B	1750	30	7	1.5	NPT	
K224A	K4224A	K4224B	780	80	18	2	NPT	
KK224A	KK4224A	KK4224B	780	100	23	2	NPT	
L224A	L4224A	L4224B	640	135	31	2	NPT	
LQ224A	LQ4224A	LQ4224B	640	135	31	2.5	Flange	
LL224A	LL4224A	LL4224B	520	140	32	3	Flange	
LS224A	LS4224A	LS4224B	640	200	45	3	Flange	
Q224A	Q4224A	Q4224B	520	300	68	4	Flange	
QS224A	QS4224A	QS4224B	520	500	114	6	Flange	
M224A	M4224A	—	420	420	95	4	Flange	
N324A	N4324A	—	350	600	136	6	Flange	
R324A	R4324A	—	280	1100	250	8	Flange	
RS324A	RS4324A	—	280	1600	363	10	Flange	

Jacketed bracket and jacketed head are standard.

CURVES



PORTING

- Right Angle (90°) (Rotatable Casing), H-Q & M
- Opposite (180°), QS-RS
- NPT / BSP
- Flanged (ANSI)

SEALING

- Packing
- Behind the Rotor Seal
- Component Mechanical Seal
- Cartridge Mechanical Seal
- Cartridge Triple Lip Seal

MOUNTING

- Foot Mount

OPTIONS

- Ductile Iron (Series 226A, 4226A)

DRIVES

- Ⓡ Offset Gear Reducer Drive
- Ⓟ Purchased Gear Reducer Drive
- ⓓ Direct-Mounted Drive (H-HL)
- Ⓥ V-Belt Drive

LIQUIDS

- Asphalt & Bitumens
- Chocolate
- Molasses
- Heavy Fuel Oil
- Waxes
- Rubber Solution



VIKING PUMP®

VIKING PUMP, INC.

A Unit of IDEX Corporation
406 State Street
Cedar Falls, Iowa 50613 U.S.A.
vikingpump.com

Brown Brothers Engineers Ltd

0508 4 BBENG
www.brownbros.co.nz

United States
vikingpump.com

Cedar Falls, Iowa
Phone: (319) 266-1741

Canada
vikingpumpcanada.com

Windsor, Ontario
Phone: (519) 256-5438

Europe & Africa
vikingpump.com

Shannon, Ireland
Phone: +353 (61) 471933

Asia-Pacific
idexfmi-asia.com

China - Shanghai
Phone: +86-21-5241-5599
India - Mumbai
Phone: +91-22-6643-5563
Singapore
Phone: +65-6684-7305

Middle East
vikingpump.com

Dubai, UAE
Phone: +971 4 2600300

Latin America
vikingpump.com

Australia & New Zealand
vikingpump.com