



MOTOR SPEED PRODUCT LINE

SERIES: 4197

STAINLESS STEEL CONSTRUCTION

FEATURES & BENEFITS

- For corrosion resistance over a wider pH range
- Non-galling gear materials standard for handling thin liquid applications
- Compact gear pump series to fit tight space constraints



CAPACITY

to 75 GPM
(17 m³/h)



PRESSURE

to 200 PSI
(14 BAR)



TEMPERATURE

0°F to +350°F
(-20°C to +175°C)



VISCOSITY

28 to 25,000 SSU
(1 to 5,500 cSt)




VIKING PUMP®

PERFORMANCE

MODELS	SPECIFICATIONS				
	Foot Mount	Performance			Standard Ports
Mechanical Seal	Max Speed, RPM	GPM	m ³ /h	Size, Inches	Type
GG4197	1750	10	2.3	1	Flange
HJ4197	1750	20	4.5	1.5	Flange
HL4197	1750	30	6.8	1.5	Flange
AS4197	1150	35	8	3	Flange
AK4197	1150	50	11	3	Flange
AL4197	1150	75	17	3	Flange

CURVES



PORTING

- Opposite (180°)
- Flanged (ANSI)

SEALING

- Behind the Rotor Seal
- Balanced Seal

MOUNTING

- Foot Mount

DRIVES

-  Direct-Mounted Drive




TYPICAL APPLICATIONS

- Compressor Lubrication
- Fuels
- Lube Oils

VIKING PUMP®

VIKING PUMP, INC.

A Unit of IDEX Corporation
 406 State Street
 Cedar Falls, Iowa 50613 U.S.A.
vikingpump.com



0508 4 BBENG
www.brownbros.co.nz

United States
vikingpump.com

Cedar Falls, Iowa
 Phone: (319) 266-1741

Canada
vikingpumpcanada.com

Windsor, Ontario
 Phone: (519) 256-5438

Europe & Africa
vikingpump.com

Shannon, Ireland
 Phone: +353 (61) 471933

Asia-Pacific
idexfmt-asia.com

China - Shanghai
 Phone: +86-21-5241-5599
 India - Mumbai
 Phone: +91-22-6643-5563
 Singapore
 Phone: +65-6684-7305

Middle East
vikingpump.com

Dubai, UAE
 Phone: +971 4 2600300

Latin America
vikingpump.com

Australia & New Zealand
vikingpump.com

